



O.R.M.A. S.R.L.



Leader 32 - 40 turbine

120 m hadica, priemer 32 mm (1")

120 m hadica, priemer 40 mm (1 1/4)

Pri zavlažovaní sa hadica sama navíja na hriadel

Štandard vybavenie:



Automatické navíjanie hadice

Tlak: min. 2,5 max. 5,5 bar
min. 36 max. 80 psi




Nastavitelná hustota zavlažovania.

Návin hadice:
min. 8 max. 30 m/h




Stop zariadenie na zastavenie toku vody

Leader 32 prietok 39/80 l/min
Leader 40 prietok 57/124 l/min



Leader 32 - 120 m
s 6 , 7 and 8 mm tryskami
Leader 40 - 120 m
Sekčný sprinkler s 8 , 9 and 10mm tryskami
Sprinkler na koľosovom vozíku
Automatický zdvih vozíka



Box: 145 x 103 x 140 cm.

Hmotnosť: 210 kg



zavlažená plocha 4660 m²



ORMA	vstupný tlak	tlakový sprinkler	prietok		max. šírka závlahy	užitocná š. závlahy	dávka v mm/hod		
	bar	bar	l/min	m ³ /h	mt	85%	10m/h	20m/h	30m/h
6	4,2	3	39	2,3	33	28	7,1	3,6	2,4
	5,3	4	45	2,7	35	30	7,7	3,9	2,6
7	3,3	2	42	2,5	30	25,5	8,4	4,2	2,8
	4,6	3	52	3,1	34	29	9,2	4,6	3,1
	5,8	4	60	3,6	37	31	9,7	4,9	3,2
8	3,9	2	57	3,4	34	29	10,1	5,1	3,4
	5,0	3	69	4,1	38	32	10,9	5,5	3,6
	6,0	4	80	4,8	41	35	11,7	5,9	3,9
9	3,0	2	71	4,2	35	30	12,2	6,1	4,1
	4,2	3	87	5,2	39	33	13,4	6,7	4,5
	5,4	4	100	6	42	36	14,3	7,2	4,8
10	4,2	2	88	5,3	30	25,5	17,6	8,8	5,9
	4,9	3	107	6,4	35	30	18,3	9,2	6,1
	5,5	4	124	7,4	38	32	19,6	9,8	6,5

Kalkulácia je orientačná, založená na teoretických prepočtoch.