



O.R.M.A. S.R.L.



Leader 32 turbine

70 m hadica, priemer 32 mm (1")

Pri zavlažovaní sa hadica sama navíja na hriadel

Štandard vybavenie :



Automatické navíjanie hadice

Tlak: min. 2,5 max. 5,5 bar
min. 36 max. 80 psi



Nastavitelná hustota zavlažovania.

Návin hadice:
min. 8 max. 30 m/h




Stop zariadenie na zastavenie toku vody



Sekčný sprinkler s 5 ,6 and 7 mm tryskami

Sprinkler na kolesovom vozíku
Automatický zdvih vozíka



Box: 90 x 90 x 105 cm
36 x 36 x 42 in

Hmotnosť: kg. 122

Kapacita : 32/80 l/min



zavlažená plocha 2840 m²

ORMA	vstupný tlak	tlak v sprinklery	prietok		max.šírka závlahy	užitocná š.závlahy	dávka v mm/hod		
	bar	bar	l/min	m ³ /h	mt	85%	10m/h	20m/h	30m/h
6	3	2	32	1,9	29	25	6,6	3,3	2,2
	4,2	3	39	2,3	33	28	7,1	3,6	2,4
	5,3	4	45	2,7	35	30	7,7	3,9	2,6
7	3,3	2	42	2,5	30	26	8,4	4,2	2,8
	4,6	3	52	3,1	34	29	9,2	4,6	3,1
	5,8	4	60	3,6	37	31	9,7	4,9	3,2
8	3,9	2	57	3,4	34	29	10,1	5,1	3,4
	5,0	3	69	4,1	38	32	10,9	5,5	3,6
	6,0	4	80	4,8	41	35	11,7	5,9	3,9

Kalkulácia je orientačná, založená na teoretických prepočtoch.